

# DV-6664

## 6.4" LCD All-in-One Player



### Product Preview

A compact and rugged solution that features our reliable DV-66 MPEG-2 Player linked to a crisp 6.4" TFT LCD display. The DV-6664 can store and playback full-motion audio/video clips from high speed CompactFlash® memory cards (CF) with DVD quality audio/video output; MPEG-1, MPEG-2, JPEG, and MP3 file formats. This unit is small and light enough to be wall mounted or integrated into a full size kiosk. A high quality hardware solution at an affordable price. The unit is available with or without touch panel.

DV-6664 - w/out touch screen feature

DV-6664T - with touch screen, see touch screen specification.

### Features

- 6.4" TFT LCD display
- Touch screen option
- Supports multiple formats: MPEG-2, MPEG-1, MP3, and JPEG
- NEW - IBM MicroDrive support
- Repeat or Menu modes available
- Multiple track selection, up to 99 tracks
- Instant track response
- Stereo audio output
- Built-in stereo speakers

### Specifications

System Type:	Digital Audio/Video playback
Format:	MPEG-1 (VCD), MPEG-2(DVD), JPEG, MP3
Dimension:	5.1" (L) x 7.5" (W) x 2" (H)
Power Consumption:	13.5 Watts
Operating Current:	1.125Amps @ 12V
Operating Voltage:	12 DC
Video Output:	NTSC/PAL auto-selection
Audio Output:	MPEG-1 level 2 Stereo
Storage Format:	• MPEG-2 files require Ultra High Speed CompactFlash® Card (min. 40x or up). Data transfer rate is 1 x 150 KB per second • MPEG-1, MP3, and JPEG files require a regular CompactFlash® card • CompactFlash® cards must be FAT formatted
Storage Capacity:	128MB up to 1GB CompactFlash®

### Benefits

- Long term durability - no moving parts
- Low maintenance - no tape to rewind
- Compact design - easy to install
- Reliable storage - re-programmable CompactFlash® media
- A high cost effective multimedia hardware solution
- Available in thermoplastic housing or board level

### Applications

- POP displays
- Digital signage systems
- Interactive kiosks
- Mobile kiosks solutions

### Accessories

#### DV-66K, Keypad Controller

To connect and control the DV-66 player with an external input device, such as push buttons.

#### DV-66U, Universal Controller

To connect DV-66 player with an analog touch screen. Eight switch buttons per controller. PIR supported.

#### DV-66F, Function Selector

The function selector provides the custom options available on the DV-66 (4800 baud rate), which include:

- VGA or Composite video output
- OSD - on or off
- Volume - up and down
- Repeat or Menu mode

#### Ultra II CompactFlash® cards

For best result with the DV-66, MedeaWiz recommends using the Ultra II high speed CompactFlash® media cards.



18688 San Jose Ave., City of Industry, CA 91748  
Corporate: 626-839-1488 • FAX: 626-839-7038  
www.medeawiz.com • Email: sales@medeawiz.com