

Flexible Tube Cleaning Hoses

Construction:

Core Tube: Polyoxymethylene

Pressure Reinforcement:

2 spiral layers of high tensile steel wire

Cover:

Polyamide, blue.

Applications:

High pressure service for tube cleaning applications such as heat exchangers in the chemical and oil refining industries.

Special type hose:

Available with an additional protective stainless steel wire braid.



Order-No.	DN	size			mm	Max working pressure (psi)	Min. Burst Pressure (psi)	Min Bend radius (mm)	Weight (kg/100m)	Connection	
		mm	inch	mm						M	F
2240D-02V32	3	-02	3.0	1/8	7.0	15,950	39,875	60	0.07	M5	M4 x 1.5
2240D-025V32	4	-025	4.0	5/32	7.7	17,400	43,500	75	0.10	M7	1/4 BSP
2240D-03V32	5	-03	4.7	3/16	9.5	14,500	40,580	95	0.20	1/8 BSP	1/4 BSP
2240D-04V32	6	-04	6.3	1/4	11.5	14,500	36,230	110	0.26	1/4 BSP	1/4 BSP
2240D-05V32	8	-05	8.0	5/16	13.3	13,050	32,610	120	0.22	1/4 BSP	3/8 BSP

Temperature range: -10°C up to +70°C