

Rotary & Impact Drilling Cutters

An innovative tool for milling off difficult to remove deposits in pipes. Designed to remove the most stubborn blockages such as concrete, cement and hard scale.

Provided with carbide/diamond tipped teeth the cutter heads 14.100 upwards have a powerful hammer action (600-3000 impacts per minute) to give a high impact and effective cutting force.



Working Pressure: up to 150 Bar

Order No.	Head Diameter (mm)	Weight (kg)	Connection	Scope of Application (Ømm)	Min l/min at 100 bar
13.040	40	0.75	1/2"	42-60 mm	60
13.060	60	1.9	1"	62-80 mm	80
14.100	90	9	1"	100 mm	100
14.120	110	10	1"	120 mm	100
14.150	135	16.4	1"	150 mm	150
14.200	175	33	1"	200 mm	200
14.250	225	36	1"	250 mm	250
14.300	275	75	1"	300 mm	300
14.350	325	-	1"	350 mm	300
14.400	375	-	1" or 1 1/4"	400 mm	300
14.450	425	-	1" or 1 1/4"	450 mm	400
14.500	475	-	1" or 1 1/4"	500 mm	450
14.600	575	102	1" or 1 1/4"	600 mm	500

Cutters 13.040 & 13.060 - Rotary only. No Impact/Hammer action.

Cutters 14.100 upwards - Rotary only or Rotary and Impact/Hammer action.

It is recommended that a rotating joint/ swivel be used on cutters 14.100 and upwards.