

Hoses

Construction:

Core Tube: Polyethylene compound, grey.

Pressure Reinforcement:

2 braided layers of high tensile synthetic yarn

Cover:



Polyurethane compound

Colour: yellow



Applications:

Hydrodynamic cleaning of sewers.

Order-No.	DN	size	inch	mm	Max working pressure (psi)	Min. Burst Pressure (psi)	Min Bend radius (mm)	Weight (kg/100m)
								
ESH-08	12	-08	1/2	19.4	2900	7250	100	23.1
ESH-12	20	-12	3/4	29.5	2900	7250	125	36.5
ESH-16	25	-16	1	36.3	2900	7250	150	59.3
ESH-20	32	-20	1 1/4	46.0	2900	7250	225	88.5

Temperature range: -10°C up to +50°C

Length Availability and Fittings:

Order-No.	Length (m)					End Fittings		
	Standard					max.	BSP Female Swivel	Bsp Male
	80	100	120	150	180			
ESH-08	▪	▪	▪			350	G 1/2	G 1/2
ESH-12		▪	▪			350	G 3/4	G 3/4
ESH-16	▪	▪	▪	▪	▪	350	G 1	G 1
ESH-20	▪	▪	▪	▪	▪	350	G 1 1/4	G 1 1/4

Adaptors



A wide range of adaptors is available for all thread sizes and working pressures.