

# SG Swivels

SG-P12P12-M-0°



SG-A12AV12-0°



SG-P12K-M-0°



SPECIFICATIONS	SG P8P8	SG P12P12-M	SG A12AV12	SG A16A16	SG CCN P12K	SG CCN A12K
Max. Pressure	15 Kpsi 1000 bar	15 Kpsi 1000 bar	20 Kpsi 1380 bar	20 Kpsi 1380 bar	15 Kpsi 1000 bar	20 Kpsi 1380 bar
Rotation Speed, Max.	600 rpm	500 rpm	600 rpm	500 rpm	2,000 rpm	2,000 rpm
Flow Rating	2.3 Cv	5.0 Cv	2.0 Cv	5.0 Cv	2.3 Cv	2.0 Cv
Flow Capacity	50 gpm 190 l/min	110 gpm 420 l/min	50 gpm 190 l/min	110 gpm 420 l/min	50 gpm 190 l/min	50 gpm 190 l/min
Inlet Port	1/2 npt	3/4 npt	3/4 MP*	1 MP*	3/4 npt	3/4 MP*
Shaft Connection	1/2 npt	3/4 npt	3/4 MP*	1 MP*	K **	K **
Length Overall	6.6 in. 17 cm	6.6 in. 17 cm	7.9 in. 20 cm	9.0 in. 23 cm	7.0 in. 17 cm	7.0 in. 20 cm
Weight	8.4 lb 3.8 kg	8.4 lb 3.8 kg	8.8 lb 4.0 kg	8.8 lb 4.0 kg	8.4 lb 3.8 kg	8.4 lb 4.0 kg
Seal Type	1/2 in. OD Plastic	5/8 in. OD Plastic	1/2 in. OD Plastic	5/8 in. OD Plastic	Carbide	Carbide

# SL Swivels

SL-P8P4-0°



SL-A9AV9-90°



SL-A9AV9-0°



## Specifications

Model	SL-P8P4	SL-A9AV9
Max. Pressure	15 Kpsi 1000 bar	20 Kpsi 1380 bar
Rotation Speed, Max.	1000 rpm	800 rpm
Shaft Connection	1/4 npt	9/16 MP
Inlet Port	1/2 npt	9/16 MP
Flow Rating	1.6 Cv	1.1 Cv
Flow Capacity	35 gpm 130 l/min	25 gpm 95 l/min
Pressure Drop at 10 gpm	40 psi 2.8 bar	80 psi 5.5 bar
Pressure Drop at 20 gpm	156 psi 11 bar	330 psi 23 bar
Torque at 10 Kpsi	5 in-lb 0.5 N-m	4 in-lb 0.4 N-m
Length Overall	4.6 in. 12 cm	5.9 in. 13 cm
Weight	1.63 lb 0.74 kg	2.00 lb 0.89 kg

- 0° or 90° inlet port
- Easily maintained seal
- Sealed, lubricated ball bearings
- Stainless steel construction
- Low torque, easy to rotate