

SH Swivel

Don't fight hose twist! SH Hose Swivel eases hose handling

Specifications

Model	SH -P8P8	
Max. Pressure	15 Kpsi	1,000 bar
Rotation Speed, Max.	250 rpm	
Body Diameter	2.25 in.	57 mm
Inlet Port	1/2 npt	
Shaft Connection	1/2 npt	
Flow Rating	2.3 Cv	
Flow Capacity	50 gpm	190 l/min
Length	4-1/8 in.	10.5 cm
Weight	1.9 lb	0.9 kg



SM Swivel

The biggest capacity swivels made

Designed like a big **SG Swivel**, the **SM**s handle up to 3500 earth-shaking horsepower. They are used in a variety of tools for cleaning boilers, furnaces, tube bundles, large tanks and vessels. Inlet port 0° or 90° option.

Specifications

Model	SM-P16	SM-P20
Max. Pressure	10 Kpsi 690 bar	10 Kpsi 690 bar
Rotation Rate, Max.	300 rpm	300 rpm
Inlet Port	1 npt	1-1/4 npt
Outlet Shaft	1 npt	1-1/4 npt
Flow Capacity	300 gpm 1100 l/min	600 gpm 2270 l/min
Flow Rating	13 Cv	18 Cv
Pressure Drop @ Flow	240 psi @ 200 gpm	490 psi @ 400 gpm
Length Overall - 0°	7.3 in. 19 cm	7.3 in. 19 cm
Length Overall - 90°	7.9 in. 20 cm	7.9 in. 20 cm
Body Diameter	3.5 in. 8.9 cm	3.5 in. 8.9 cm
Weight	13 lb 6 kg	13 lb 6 kg



UH-H9H6 Swivel

Rugged dependability in an ultra-high pressure swivel

Handles pump power up to 450 HP, inlet port 0° or 90° option.

Specifications

Model	UH-H9H6	
Max. Pressure	40 Kpsi	2,760 bar
Rotation Speed, Max.	1,500 rpm *	
Body Diameter	2.5 in.	64 mm
Inlet Port	9/16 HP	
Shaft Connection	3/8 HP	
Flow Rating	0.64 Cv	
Flow Capacity	20 gpm	76 l/min
Length	8.75 in.	22.2 cm
Weight	7.5 lb	3.4 kg

* Break-in new seals for 1/2 hr. at 500 rpm max.

