

## Water Source Heat Pumps

Type *Cassette*

Capacity 1.600 and 2.100 Watts Total cooling

Model K7RO-7C.00.16 and 21

# K7RO

# R407C



### Standard

- ☞ Electrical connections by snap connectors
- ☞ Acoustic isolation to M1
- ☞ Reinforced acoustic treatment
- ☞ Anti-vibration mounts
- ☞ Condensate lift pump
- ☞ Supply and return air grille to RAL 9010 satin texture
- ☞ 4-way supply with manually adjustable vanes
- ☞ Options for ducted discharge : 2 x 125 diameter or 1 x 160 diameter
- ☞ Master / Slave option { except for digital control by GTC }

### Options

- ☞ Cooling only
- ☞ Constant pressure valve
- ☞ Electric resistance heating
- ☞ RAL finish to choice, dependant upon quantity
- ☞ Fresh air connection for 1 x 125 diameter
- ☞ Controls: See table below

### Controls

**Electronic Thermostat** : AD 98.01

Automatic or manual changeover – Adjustable dead band  
Stop / Start switch – Three fan speeds  
Heating, cooling, fault indication – Night override

**Digital display** : ACR 12

**Digital** : Remote control via GTC on application



AD 98.01



ACR 12

*FRANCE ENERGIE reserves the right to change this document at any time without consultation. This document is non-contractual*