

# MIXRITE PROPORTIONING PUMP

## MIXRITE™ 2502 PROPORTIONING PUMP

### WITH AIR RELEASE VALVE

<b>Additive mixing range</b>	<b>0.2 – 2.0%</b> <b>(1:500 – 1:50)</b>
<b>Operating pressure</b>	<b>0.2 – 6.0BAR</b> <b>(2.9 – 85.0 PSI)</b>
<b>Flow rate</b>	<b>20 – 2,500 lt/h</b> <b>(4.4 - 550 gal/h)</b>

- High resistance to U.V. radiation
- Quick, easy and accurate adjustment
- Durable body and cover made from Nylon12 reinforced with 30% fibreglass
- Piston seals made from Nylon12 (Good chemical resistance) and Teflon (Non stick)
- Suction cylinder made from PEHD
- Built-in stoppers and ribs in the suction cylinder in order to avoid over dosing damages
- Suction filter made from chemical resistant Polypropylene
- Red sleeve indicates that the medicator is supplied with special poultry features
- Driven by water alone, no electrical parts
- Low cost replacement parts



DALTON ENGINEERING - POULTRY KNOW-HOW



Dalton Engineering, Dalton Lane, Dalton, Thirsk  
North Yorkshire YO7 3HR  
Tel: 01845 578 325 Fax: 01845 577 841  
Email: [info@daltonengineering.co.uk](mailto:info@daltonengineering.co.uk)  
[www.daltonengineering.co.uk](http://www.daltonengineering.co.uk)