



SAFETY DATA SHEET TREADFAST UNITEX PART B

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME	TREADFAST UNITEX PART B
PRODUCT NO.	10520
APPLICATION	One part of a multi-part smoothing underlayment for floors
SUPPLIER	Tremco illbruck Production Limited Coupland Road Hindley Green Wigan WN2 4HT England Tel: (+44) 1942 258011
CONTACT PERSON	R P Brisbourne
EMERGENCY TELEPHONE	(+44) 1942 258011

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
AMMONIA, ANHYDROUS	231-635-3	7664-41-7	< 0.5%	R10 T;R23 C;R34 N;R50
NATURAL RUBBER LATEX	232-689-0	9006-04-6	10-30%	R43.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact.

CLASSIFICATION R43.

HUMAN HEALTH

May cause a allergic reaction in individuals sensitive to rubber latex

4 FIRST-AID MEASURES

INHALATION

Move into fresh air and keep at rest.

INGESTION

Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention.

SKIN CONTACT

Wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Rinse with water. Contact physician if discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

The product is non-combustible.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

TREADFAST UNITEX PART B

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid skin and eye contact Persons with a known allergy to rubber latex should not handle this product.

STORAGE PRECAUTIONS

No special storage precautions noted.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
AMMONIA, ANHYDROUS	WEL	25 ppm	18 mg/m3	35 ppm	25 mg/m3

PROTECTIVE EQUIPMENT



HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	White		
ODOUR	Ammonia		
SOLUBILITY	Miscible with water.		
BOILING POINT (°C)	100° 760 mm Hg	RELATIVE DENSITY	0.95 @ 25° °c
pH-VALUE, CONC. SOLUTION	10.1	FLASH POINT (°C)	N/A N/A.
AUTO IGNITION TEMPERATURE (°C)	N/A		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

MATERIALS TO AVOID

Strong acids. Metals

HAZARDOUS DECOMPOSITION PRODUCTS

No specific hazardous decomposition products noted.

11 TOXICOLOGICAL INFORMATION

SKIN CONTACT

May cause skin irritation/eczema

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

May cause sensitisation by skin contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

TREADFAST UNITEX PART B

ACUTE FISH TOXICITY
Low toxicity to aquatic organisms

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Product is not classified as hazardous waste according to the Hazardous Waste Regulations (2005)

DISPOSAL METHODS

Do not allow runoff to sewer, waterway or ground.

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL Not classified as hazardous for transport

15 REGULATORY INFORMATION

LABELLING



Irritant

CONTAINS NATURAL RUBBER LATEX

RISK PHRASES

R43 May cause sensitisation by skin contact.

SAFETY PHRASES

S24 Avoid contact with skin.

S37 Wear suitable gloves.

16 OTHER INFORMATION

REVISION COMMENTS

Changes from the previous edition of this sheet are marked by a line in the margin.

REVISION DATE 13/10/2006

REV. NO./REPL. SDS GENERATED 20/09/2004

RISK PHRASES IN FULL

R10 Flammable.
R23 Toxic by inhalation.
R34 Causes burns.
R37 Irritating to respiratory system.
R43 May cause sensitisation by skin contact.
R50 Very toxic to aquatic organisms.